



Power Dekor Ltd
6/63 Arrenway Drive, Rosedale, 0632
Auckland, New Zealand
PO Box 101552, NSMC
Phone: 09-4448288
Info@powerdekorgroup.co.nz
www.powerdekorfloors.co.nz
GST: 112-088-679

Power Dekor Laminate Flooring Maintenance/Care Instruction

How To Protect Your Floor

1. After the installation is completed, pay attention to maintaining air circulation, not to close doors and windows. Furniture should be installed after 48 hours and then move in; the surface of the floor should not symmetrically place overweight objects.
2. It is crucial to maintain humidity level at 35%-70% in flooring area; high humidity will cause the floor arch, the sound, the humidity is too low will cause the floor serious cracking, delamination, warped, deformation.
3. It is a wood-based flooring, high temperature from direct sunlight may case issues with dimensional stability. Window tinted or curtain are strongly recommended for areas that receives a lot of direct sunlight, please do keep the curtain closed during the peak sunlight hours.
4. Use non-staining felt protectors under heavy pieces of furniture. Fit office chairs, furniture, with soft treads or castors. Chair pad should be used under deck chairs with castors.

5. Never drag, slide or roll furniture or appliances across your floor. Protect the surface by using a trolley to move heavy objects.
6. Pat claws can scratch your floor, so please keep nails trimmed.
7. Floor to ceiling windows/doors with New Zealand Sun can create floor surface temperature over 70°C. Power Dekor AquaREPEL Laminate Flooring is manufactured to be stable in between 0-40°C. Therefore, your floor should be protected from extreme temperatures and strong direct sunlight using interior temperature and humidity control (recommended temperatures 10-30°C and relative humidity levels between 35-70%, window tinting, awnings, or curtains/blinds. Dramatic temperature changes or extreme humidity can cause joints to lip, buckle and fading.
8. The surface of the floor should not be covered with airtight material for a long time and prevent the sun from exposure for a long time, avoid discoloration.

How to Clean and Care

1. Clean up any liquid or water spills or any other potentially staining marks using a dry clean cloth. Even though Power Dekor AquaREPEL Laminate Floor is water-resistant with splash and spills, do not leave liquid/water just to test it. Though Power Dekor AquaREPEL Laminate Floors are resistant to most spots and stains, some materials, or colorants (such as tar, grease, oil, dyes, waxes, ball points marker pens, pet mishaps or foods/beverages containing strong dyes such as mustard, curry, cordial, coffee, tea etc,) may under certain conditions migrate into the wear layer causing indelible stains.
2. Prohibited use of alcohol (unless authorized by the Power Dekor), banana water, acid, alkaline solvent, or organic solvent such as gasoline to clean the floor.
3. Steam mopping is permitted to clean the floor but not recommended for often cleaning (three times a month is advised). It is recommended to use a vacuum to clean the dust first, apply dry mop with less water/or Laminate flooring cleaner (Neutral PH) to clean the floor. Power Dekor can supply the mop kit by your order.

4. Never use abrasive cleaners, nylon scouring pads, steel wool, scouring powder or bleach as they may damage the floor.
5. Never use oil, soap, wax or polishes as these finishes may make the floor slippery and can leave a dull finish on the floor.

Even though Power Dekor AquaREPEL Laminate Floorings are exceptionally stable, boards can still be subject to some shrinkage and growth during changes in climatic conditions leading to small gaps between planks. Gaps should not exceed 0.15% of boards length. This is a normal feature of laminate floors and not considered a manufacturing defect.